

Technical Data		Audi Q4 e-tron Sportback 35 125 kW	
Program for Germany		Status: 05/10/21	
Engine / electrics			
Peak electrical output in kW (PS)		125 (170)	
Continuous electrical output in kW		70	
Electrical torque output in Nm (<i>lb-ft</i>)		310 (228.6)	
Battery type		Lithium-ion	
Battery capacity gross / net in kWh		55 / 51.5	
12V battery in A / Ah		280 / 51	
On-board voltage 1 in volts		400	
Drivetrain / transmission			
Drive type		Rear-wheel drive	
Transmission type		1-speed / automatic	
Suspension / steering / brakes			
Type and design of front-axle suspension		MacPherson struts, front	
Type and design of rear-axle suspension		4-link rear axle	
Steering		Electromechanical steering with speed-dependent power assistance	
Steering ratio		15.6	
Turning circle in m (<i>ft</i>)		10.2 (33.5)	
Brake control system		Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic) front rear		235/55 R 19 255/50 R 19	
Wheels (basic) front rear		Alloy 8 J x 19" 8 J x 19"	
Performance / acoustics			
Top speed in km/h (<i>mph</i>)		160 (99.4)	
Limited		yes	
Electrical acceleration, 0-100 km/h (<i>62.1 mph</i>) in s		9.0	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)		- / 66	
Consumption / range			
Electric power consumption, combined, in kWh/100 km (<i>62.1 mi</i>) *		18.6 - 16.6 (WLTP) 16.6 - 15.6 (NEDC)	
CO2 emissions, combined, in g/km (<i>g/mi</i>)		0	
Electrical range, combined according to WLTP in km (<i>mi</i>) *		349 - 314 (216.9 - 195.1)	
Servicing / guarantee (Germany)			
Service interval		2 years	
Vehicle / paint / rust perforation guarantee		2 / 3 / 12 (years)	
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive		16 / 22 / 22	
Weights / loads			
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)		1895 (4177.8) / 1970 (4343.1) / 2475 (5456.4)	
Front/rear axle load limit in kg (<i>lb</i>)		1145 (2524.3) / 1400 (3086.5)	
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)		1000 (2204.6) / 1000 (2204.6) // 750 (1653.5)	
Roof load limit / permissible nose weight in kg (<i>lb</i>)		75 (165.3) / 75 (165.3)	

Capacities	
Cooling system capacity (incl. heating) in l (US gal)	10.5 (2.8)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (sq ft)	0.27 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (ft)	4588 (15.1) / 1865 (6.1) / 1614 (5.3) / -
Width including mirrors in mm (ft)	2108 (6.9)
Wheelbase / track width front/rear in mm (ft)	2764 (9.1) / 1587 (5.2) / 1565 (5.1)
Overhang angle of steel springs, front/rear in degrees	19.40 / 16.90
Height of loading edge with steel springs / air springs in mm (ft)	783 (2.6) / -
Open luggage compartment - behind the 2nd seat row in l (cu ft)	535 (18.9)
Largest luggage capacity - behind the 1st seat row in l (cu ft)	1460 (51.6)

* Figures depend on the equipment selected.

Technical Data	Audi Q4 e-tron Sportback 50 quattro 220 kW
Program for Germany	Status: 05/10/21
Engine / electrics	
Peak electrical output in kW (PS)	220 (299)
Continuous electrical output in kW	77
Electrical torque output in Nm (<i>lb-ft</i>)	460 (339.3)
Battery type	Lithium-ion
Battery capacity gross / net in kWh	82 / 76.6
12V battery in A / Ah	280 / 51
On-board voltage 1 in volts	400
Drivetrain / transmission	
Drive type	All-wheel drive
Transmission type	1-speed / automatic
Suspension / steering / brakes	
Type and design of front-axle suspension	MacPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.6
Turning circle in m (<i>ft</i>)	11.5 (37.7)
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic) front rear	235/55 R 19 255/50 R 19
Wheels (basic) front rear	Alloy 8 J x 19" 8 J x 19"
Performance / acoustics	
Top speed in km/h (<i>mph</i>)	180 (111.8)
Limited	yes
Electrical acceleration, 0-100 km/h (<i>62.1 mph</i>) in s	6.2
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 66
Consumption / range	
Electric power consumption, combined, in kWh/100 km (<i>62.1 mi</i>)*	20.9 - 17.6 (WLTP) 17.9 - 16.4 (NEDC)
CO2 emissions, combined, in g/km (<i>g/mi</i>)	0
Electrical range, combined according to WLTP in km (<i>mi</i>)*	497 - 420 (308.8 - 261.0)
Servicing / guarantee (Germany)	
Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 24 / 22
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2140 (4717.9) / 2215 (4883.2) / 2715 (5985.6)
Front/rear axle load limit in kg (<i>lb</i>)	1275 (2810.9) / 1510 (3329.0)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1200 (2645.5) / 1200 (2645.5) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 (165.3) / 75 (165.3)

Capacities	
Cooling system capacity (incl. heating) in l (US gal)	11.5 (3.0)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (sq ft)	0.27 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (ft)	4588 (15.1) / 1865 (6.1) / 1614 (5.3) / -
Width including mirrors in mm (ft)	2108 (6.9)
Wheelbase / track width front/rear in mm (ft)	2764 (9.1) / 1587 (5.2) / 1565 (5.1)
Overhang angle of steel springs, front/rear in degrees	19.40 / 16.90
Height of loading edge with steel springs / air springs in mm (ft)	783 (2.6) / -
Open luggage compartment - behind the 2nd seat row in l (cu ft)	535 (18.9)
Largest luggage capacity - behind the 1st seat row in l (cu ft)	1460 (51.6)

* Figures depend on the equipment selected.