

Technical Data		Audi A4 allroad quattro 45 TFSI S tronic (180 kW)	
Program for Germany		Status: 06/08/2019	
Engine / electrics			
Engine type	Inline 4-cylinder engine		
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment / 2/2 inlet/exhaust valves per cylinder		
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.6		
Max. power output in kW (PS) / rpm	180 (245) / 5000 - 6500		
Max. torque in Nm (lb-ft) / at rpm	370 (272.9) / 1600 - 4300		
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler		
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter		
Emissions standard	EU6		
Start-stop / REM	yes / yes		
Battery in A / Ah	340 / 58		
Max. electrical output at 12V in kilowatts	3.1		
On-board voltage 1 in volts	12		
Drivetrain / transmission			
Drive type	quattro all-wheel drive with ultra technology		
Type of center differential	Electronically controlled multi-plate clutch		
Type of rear axle differential	quattro ultra		
Clutch	Dual clutch		
Transmission type	7-speed S tronic / dual clutch		
Transmission ratio in 1st/2nd gear	3.188 / 2.190		
Transmission ratio in 3rd/4th gear	1.517 / 1.057		
Transmission ratio in 5th/6th gear	0.738 / 0.557		
Transmission ratio in 7th/8th gear	0.433 / -		
Reverse gear ratio / final drive ratio 1-2	2.750 / 4.410		
Suspension / steering / brakes			
Type and design of front-axle suspension	Five-link front suspension; tubular anti-roll bar		
Type and design of rear-axle suspension	Five-link rear suspension; tubular anti-roll bar		
Steering	Electromechanical steering with speed-dependent power assistance		
Steering ratio min. / max.	15.9 / 15.9		
Steering ratio min. / max. optional	10.0 / 16.0		
Turning circle / turning circle optional in m (ft)	11.7 (38.4) / not available		
Brake control system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist		
Tires (basic)	225/55 R 17 97 Y		
Wheels (basic)	Forged aluminum 7.5Jx17"		
Performance / acoustics			
Top speed in km/h (mph)	247 (153.5)		
Limited	yes		
Acceleration, 0-100 km/h (0-62.1 mph)	6.1		
Fuel type / octane value	Gasoline / 95		
Fuel standard	DIN EN 228 not available		
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in dB (A)	68.4 / - / 68		

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined in liters per 100 kilometers (<i>US mpg</i>)	8.6-8.4 (27.4-28.0) / 5.8-5.5 (40.6-42.8) / 6.8-6.6 (34.6-35.6)
CO ₂ emissions combined in grams per kilometer (<i>g/mi</i>)	155-150 (249.4-241.4)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	14 / 22 / 22
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1615 (3560.5) / 1690 (3725.8) / 2200 (4850.2)
Front/rear axle load limit in kg (<i>lb</i>)	1085 (2392.0) / 1215 (2678.6)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1900 (4188.8) / 1700 (3747.9) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	90 (198.4) / 80 (176.4)
Capacities	
Cooling system capacity (incl. heating) in liters (<i>US gal</i>)	8.4 (2.2)
Engine oil capacity, including filter (change volume) in liters (<i>US qt</i>)	5.2 (5.5)
Fuel tank capacity in liters (<i>US gal</i>)	58 (15.3)
Dimensions / body	
Body type / number of doors	Unitary steel/aluminum composite construction / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.32 / 2.24 (24.1)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4762 (15.6) / 1847 (6.1) / 1493 (4.9) / -
Width including mirrors in mm (<i>ft</i>)	2022 (6.6)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2818 (9.2) / 1578 (5.2) / 1566 (5.1)
Overhang angle of steel springs, front/rear in degrees	14.70 / 16.80
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	663 (2.2) / -
Luggage capacity behind 2nd seat bench, open / closed in l (<i>cu ft</i>)	495 (17.5) / not available
Largest luggage compartment capacity - behind the 1st seat row in l (<i>cu ft</i>)	1495 (52.8)
Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	495 (17.5)

* Fuel consumption and CO₂ emission figures given in ranges depend on the tires/wheels used