

<b>Technical Data</b>		<b>Audi Q4 e-tron 35 125 kW</b>	
<b>Program for Germany</b>		Status: 05/10/21	
<b>Engine / electrics</b>			
Peak electrical output in kW (PS)	125 (170)		
Continuous electrical output in kW	70		
Electrical torque output in Nm ( <i>lb-ft</i> )	310 (228.6)		
Battery type	Lithium-ion		
Battery capacity gross / net in kWh	55 / 51.5		
12V-Battery in A / Ah	280 / 51		
On-board voltage 1 in volts	12		
On-board voltage 2 in volts	400		
<b>Drivetrain / transmission</b>			
Drive type	Rear-wheel drive		
Transmission type	1-speed / automatic		
<b>Suspension / steering / brakes</b>			
Type and design of front-axle suspension	MacPherson struts, front		
Type and design of rear-axle suspension	4-link rear axle		
Steering	Electromechanical steering with speed-dependent power assistance		
Steering ratio	15.6		
Turning circle in m ( <i>ft</i> )	10.2 (33.5)		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic) front   rear	235/55 R 19   255/50 R 19		
Wheels (basic) front   rear	Alloy 8 J x 19"   8 J x 19"		
<b>Performance / acoustics</b>			
Top speed in km/h ( <i>mph</i> )	160 (99.4)		
Limited	yes		
Electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in s	9.0		
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 66		
<b>Consumption / range</b>			
Electric power consumption, combined, in kWh/100 km (62.1 <i>mi</i> )*	19.1 - 17.0 (WLTP) 16.7 - 15.8 (NEDC)		
CO2 emissions, combined, in g/km ( <i>g/mi</i> )	0		
Electrical range, combined according to WLTP in km ( <i>mi</i> )*	341 - 306 (211.9 - 190.1)		
<b>Servicing / guarantee (Germany)</b>			
Service interval	2 years		
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)		
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 22 / 22		
<b>Weights / loads</b>			
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1890 (4166.7) / 1965 (4332.1) / 2475 (5456.4)		
Front/rear axle load limit in kg ( <i>lb</i> )	1145 (2524.3) / 1395 (3075.4)		
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1000 (2204.6) / 1000 (2204.6) // 750 (1653.5)		
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 75 (165.3)		

<b>Capacities</b>	
Cooling system capacity (incl. heating) in l ( <i>US gal</i> )	10.5 (2.8)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.28 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4588 (15.1) / 1865 (6.1) / 1632 (5.4) / -
Width including mirrors in mm ( <i>ft</i> )	2108 (6.9)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2764 (9.1) / 1587 (5.2) / 1565 (5.1)
Overhang angle of steel springs, front/rear in degrees	19.40 / 16.90
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	783 (2.6) / -
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	520 (18.4)
Largest luggage capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1490 (52.6)

\* Figures depend on the equipment selected.

<b>Technical Data</b>		<b>Audi Q4 e-tron 40 150 kW</b>	
<b>Program for Germany</b>		Status: 04/20/21	
<b>Engine / electrics</b>			
Peak electrical output in kW (PS)	150 (204)		
Continuous electrical output in kW	70		
Electrical torque output in Nm ( <i>lb-ft</i> )	310 (228.6)		
Battery type	Lithium-ion		
Battery capacity gross / net in kWh	82 / 77		
12V-Battery in A / Ah	280 / 51		
On-board voltage 1 in volts	12		
On-board voltage 2 in volts	400		
<b>Drivetrain / transmission</b>			
Drive type	Rear-wheel drive		
Transmission type	1-speed / automatic		
<b>Suspension / steering / brakes</b>			
Type and design of front-axle suspension	MacPherson struts, front		
Type and design of rear-axle suspension	4-link rear axle		
Steering	Electromechanical steering with speed-dependent power assistance		
Steering ratio	15.6		
Turning circle in m ( <i>ft</i> )	10.2 (33.5)		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic) front   rear	235/55 R 19   255/50 R 19		
Wheels (basic) front   rear	Alloy 8 J x 19"   8 J x 19"		
<b>Performance / acoustics</b>			
Top speed in km/h ( <i>mph</i> )	160 (99.4)		
Limited	yes		
Electrical acceleration, 0-100 km/h ( <i>62.1 mph</i> ) in s	8.5		
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 66		
<b>Consumption / range</b>			
Electric power consumption, combined, in kWh/100 km ( <i>62.1 mi</i> )*	19.3 - 17.3 (WLTP) 17.3 - 16.3 (NEDC)		
CO2 emissions, combined, in g/km ( <i>g/mi</i> )	0		
Electrical range, combined according to WLTP in km ( <i>mi</i> )*	520 - 466 (323.1 - 289.6)		
<b>Servicing / guarantee (Germany)</b>			
Service interval	2 years		
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)		
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 22 / 22		
<b>Weights / loads</b>			
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2050 (4519.5) / 2125 (4684.8) / 2640 (5820.2)		
Front/rear axle load limit in kg ( <i>lb</i> )	1195 (2634.5) / 1505 (3318.0)		
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1000 (2204.6) / 1000 (2204.6) // 750 (1653.5)		
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 75 (165.3)		

<b>Capacities</b>	
Cooling system capacity (incl. heating) in l ( <i>US gal</i> )	10.3 (2.7)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.28 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4588 (15.1) / 1865 (6.1) / 1632 (5.4) / -
Width including mirrors in mm ( <i>ft</i> )	2108 (6.9)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2764 (9.1) / 1587 (5.2) / 1565 (5.1)
Overhang angle of steel springs, front/rear in degrees	19.40 / 16.90
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	783 (2.6) / -
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	520 (18.4)
Largest luggage capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1490 (52.6)

\* Figures depend on the equipment selected.

<b>Technical Data</b>		<b>Audi Q4 e-tron 50 quattro 220 kW</b>	
<b>Program for Germany</b>		Status: 05/12/21	
<b>Engine / electrics</b>			
Peak electrical output in kW (PS)	220 (299)		
Continuous electrical output in kW	77		
Electrical torque output in Nm ( <i>lb-ft</i> )	460 (339.3)		
Battery type	Lithium-ion		
Battery capacity gross / net in kWh	82 / 76.6		
12V battery in A / Ah	280 / 51		
On-board voltage 1 in volts	12		
On-board voltage 2 in volts	400		
<b>Drivetrain / transmission</b>			
Drive type	All-wheel drive		
Transmission type	1-speed / automatic		
<b>Suspension / steering / brakes</b>			
Type and design of front-axle suspension	MacPherson struts, front		
Type and design of rear-axle suspension	4-link rear axle		
Steering	Electromechanical steering with speed-dependent power assistance		
Steering ratio	15.6		
Turning circle in m ( <i>ft</i> )	11.5 (37.7)		
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist		
Tires (basic) front   rear	235/55 R 19   255/50 R 19		
Wheels (basic) front   rear	Alloy 8 J x 19"   8 J x 19"		
<b>Performance / acoustics</b>			
Top speed in km/h ( <i>mph</i> )	180 (111.8)		
Limited	yes		
Electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in s	6.2		
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 66		
<b>Consumption / range</b>			
Electric power consumption, combined, in kWh/100 km (62.1 <i>mi</i> )*	20.0 - 17.9 (WLTP) 17.8 - 16.5 (NEDC)		
CO2 emissions, combined, in g/km ( <i>g/mi</i> )	0		
Electrical range, combined according to WLTP in km ( <i>mi</i> )*	488 - 443 (303.2 - 275.3)		
<b>Servicing / guarantee (Germany)</b>			
Service interval	2 years		
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)		
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 24 / 22		
<b>Weights / loads</b>			
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2135 (4706.9) / 2210 (4872.2) / 2720 (5996.6)		
Front/rear axle load limit in kg ( <i>lb</i> )	1270 (2799.9) / 1515 (3340.0)		
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1200 (2645.5) / 1200 (2645.5) // 750 (1653.5)		
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 (165.3) / 75 (165.3)		

<b>Capacities</b>	
Cooling system capacity (incl. heating) in l ( <i>US gal</i> )	11.5 (3.0)
<b>Dimensions / body</b>	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.28 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm ( <i>ft</i> )	4588 (15.1) / 1865 (6.1) / 1617 (5.3) / -
Width including mirrors in mm ( <i>ft</i> )	2108 (6.9)
Wheelbase / track width front/rear in mm ( <i>ft</i> )	2764 (9.1) / 1587 (5.2) / 1565 (5.1)
Overhang angle of steel springs, front/rear in degrees	19.40 / 16.90
Height of loading edge with steel springs / air springs in mm ( <i>ft</i> )	783 (2.6) / -
Open luggage compartment - behind the 2nd seat row in l ( <i>cu ft</i> )	520 (18.4)
Largest luggage capacity - behind the 1st seat row in l ( <i>cu ft</i> )	1490 (52.6)

\* Figures depend on the equipment selected.